



## 4-3/4" Drillcollar, Non-Mag. Slick, Specification Sheet

Technical for DC's	Unit	4 3/4"
Shoulder type	Taper	Slick
Overall Length (New)	ft	31
	<i>mtr</i>	<i>9,45</i>

Elevator & Slip recess OD	inch	NA
Elevator & Slip recess length	inch	NA
Spiral length	inch	NA
Box tong space	inch	NA
Pin tong space	inch	NA

Displacement	gal/ft	0,716
	<i>l/m</i>	<i>8,89</i>
Capacity	gal/ft	0,207
	<i>l/m</i>	<i>2,57</i>
Closed End Displacement	gal/ft	0,923
	<i>l/m</i>	<i>11,46</i>

Weight	lbs	1 442
	<i>kg</i>	<i>654</i>
Weight/Length	lbs/ft	46,6
	<i>kg/mtr</i>	<i>69,4</i>

<b>Connection</b>	API	NC-38
OD	inch	4,75
ID	inch	2,25
BB+SRG (NS-2)		Yes
Connection Tensile Capacity	lbf	465 000
	<i>kN</i>	<i>2 068</i>
Connection Torsional Capacity	ft-lbf	16 200
	<i>kNm</i>	<i>21,9</i>
Make up torque (with SRG)	ft-lbf	9 200
	<i>kNm</i>	<i>12,5</i>

### Body

Material Grade	P-530	
Tensile Capacity (New)	lbf	1 511 900
	<i>kN</i>	<i>6 725</i>
Torsional Capacity (New)	ft-lbs	105 700
	<i>kNm</i>	<i>143,3</i>



Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !