

**ODFJELL WELL SERVICES**  
**TECHNICAL SPECIFICATION**



<b>TUBING</b>	<b>CONNECTION</b>	<b>WEIGHT/QUALITY</b>	<b>SERVICE</b>
<b>1.660"</b>	<b>TPS TS-8 MULTISEAL</b>	<b>3,24 LB/FT, L-80</b>	<b>STANDARD</b>

**DESCRIPTION**

Pipe OD/ID/Wall thickness	1,660" x 1,264" x 0,198"
Pipe grade	L-80
Pipe weight	3.24 lb/ft / 4.83 kg/m
Joint weight	99 lb / 45 kg
Average joint length	31 ft. / 9.4 mtr.
Drift Diameter	1.170" / 29,72 mm
Connection OD	TP8-1,927"
Box OD Taper	~11°
New pipe tensile	73 000 lb / 324.720 kN
New pipe Torsional	1 830 Lb-ft / 2 480 Nm
New pipe burst	16 700 PSI / 115.142 MPa
New pipe collapse	16 810 PSI / 115.901 MPa
Connection Pressure Rating, Burst	as per new pipe
Connection Pressure Rating, Collapse	as per new pipe
Connection make-up, minimum	600 lb-ft / 815 Nm
Connection make-up, optimum	675 lb-ft / 915 Nm
Connection make-up, maximum	750 lb-ft / 1 020 Nm
Tubing Capacities:	
Closed End Displacement	1,40 l/m
Open End Displacement	0,58 l/m
Capacity	0,82 l/m