



6-3/4" Drillcollar, Non-Mag. Slick, Specification Sheet

Technical for DC's	Unit	6 3/4"
Shoulder type	Taper	Slick
Overall Length (New)	ft <i>mtr</i>	31 <i>9,45</i>

Elevator & Slip recess OD	inch	NA
Elevator & Slip recess length	inch	NA
Spiral length	inch	NA
Box tong space	inch	NA
Pin tong space	inch	NA

Displacement	gal/ft <i>l/m</i>	1,540 <i>19,13</i>
Capacity	gal/ft <i>l/m</i>	0,324 <i>4,02</i>
Closed End Displacement	gal/ft <i>l/m</i>	1,864 <i>23,15</i>

Weight	lbs <i>kg</i>	3 102 <i>1 407</i>
Weight/Length	lbs/ft <i>kg/mtr</i>	100,27 <i>149,2</i>

Connection	API	NC-50
OD	inch	6,75
ID	inch	2,813
BB+SRG (NS-2)		Yes
Connection Tensile Capacity	lbf <i>kN</i>	987 800 <i>4 393</i>
Connection Torsional Capacity	ft-lbf <i>kNm</i>	45 900 <i>62,2</i>
Make up torque (with SRG)	ft-lbf <i>kNm</i>	26 000 <i>35,2</i>

Body

Material Grade	P-530	
Tensile Capacity (New)	lbf <i>kN</i>	3 252 000 <i>14 465</i>
Torsional Capacity (New)	ft-lbs <i>kNm</i>	309 700 <i>419,9</i>



Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !