



## 8" & 8-1/4" Drillcollar, Non-Mag. Slick, Specification Sheet

Technical for DC's	Unit	8"	8-1/4"
Shoulder type	Taper	Slick	Slick
Overall Length (New)	ft	31	31
	<i>mtr</i>	<i>9,45</i>	<i>9,45</i>
Elevator & Slip recess OD	inch	NA	NA
Elevator & Slip recess length	inch	NA	NA
Spiral length	inch	NA	NA
Box tong space	inch	NA	NA
Pin tong space	inch	NA	NA
Displacement	gal/ft	2,295	2,461
	<i>l/m</i>	<i>28,5</i>	<i>30,6</i>
Capacity	gal/ft	0,324	0,324
	<i>l/m</i>	<i>4,02</i>	<i>4,02</i>
Closed End Displacement	gal/ft	2,618	2,784
	<i>l/m</i>	<i>32,52</i>	<i>34,58</i>
Weight	lbs	4 621	4 956
	<i>kg</i>	<i>2 096</i>	<i>2 248</i>
Weight/Length	lbs/ft	149,37	160,18
	<i>kg/mtr</i>	<i>222,3</i>	<i>238,4</i>
<b>Connection</b>	API	6-5/8" Reg.	6-5/8" Reg.
OD	inch	8	8,250
ID	inch	2,813	2,813
BB+SRG (NS-2)		Yes	Yes
Connection Tensile Capacity	lbf	1 456 000	1 456 000
	<i>kN</i>	<i>6 476</i>	<i>6 476</i>
Connection Torsional Capacity	ft-lbf	76 200	76 900
	<i>kNm</i>	<i>103,3</i>	<i>104,3</i>
Make up torque (with SRG)	ft-lbf	43 300	43 700
	<i>kNm</i>	<i>58,7</i>	<i>59,3</i>
<b>Body</b>			
Material Grade		P-530	
Tensile Capacity (New)	lbf	4 405 000	4 724 000
	<i>kN</i>	<i>19 594</i>	<i>21 013</i>
Torsional Capacity (New)	ft-lbs	476 000	522 900
	<i>kNm</i>	<i>645,4</i>	<i>708,9</i>



Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !