



9-1/2" Drillcollar, Non-Mag. Slick, Specification Sheet

Technical for DC's	Unit	9 1/2"
Shoulder type	Taper	Slick
Overall Length (New)	ft <i>mtr</i>	31 <i>9,45</i>

Elevator & Slip recess OD	inch	NA
Elevator & Slip recess length	inch	NA
Spiral length	inch	NA
Box tong space	inch	NA
Pin tong space	inch	NA

Displacement	gal/ft <i>l/m</i>	3,324 <i>41,28</i>
Capacity	gal/ft <i>l/m</i>	0,368 <i>4,57</i>
Closed End Displacement	gal/ft <i>l/m</i>	3,692 <i>45,85</i>

Weight	lbs <i>kg</i>	6 694 <i>3 036</i>
Weight/Length	lbs/ft <i>kg/mtr</i>	216,37 <i>322,0</i>

Connection	API	7-5/8" Reg.
OD	inch	9,500
ID	inch	3,000
BB+SRG (NS-2)		Yes
Connection Tensile Capacity	lbf <i>kN</i>	2 220 600 <i>9 878</i>
Connection Torsional Capacity	ft-lbf <i>kNm</i>	132 500 <i>179,6</i>
Make up torque (with SRG)	ft-lbf <i>kNm</i>	77 500 <i>105,0</i>

Body

Material Grade	P-530	
Tensile Capacity (New)	lbf <i>kN</i>	6 380 000 <i>28 379</i>
Torsional Capacity (New)	ft-lbs <i>kNm</i>	801 000 <i>1 086,0</i>



Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !