

**ODFJELL WELL SERVICES  
TECHNICAL SPECIFICATION**



<b>3-1/2" TUBING 533 con</b>	<b>PREMIUM</b>
------------------------------	----------------

<b>DESCRIPTION</b>	
Range	<b>2</b>
<b>PIPE BODY</b>	
OD of the pipe body	<b>3 1/2"</b>
ID of the pipe body	<b>2,548"</b>
Nominal weight	<b>15,8 lbs./ft.</b>
Plain End Weigth	<b>15,39 lbs./ft.</b>
Grade	<b>T-95</b>
Wall thicknes (nominal)	<b>0,476"</b>
Drift diameter, minimum	<b>2,423"</b>
Special Drift Diameter	<b>N/A</b>
Body Yield Strength	<b>400 x 1000 lbs</b>
80% Test Presure	<b>20.700 psi</b>
Internal Yield	<b>22.610 psi</b>
Bending Strength	<b>129 degree /100'</b>
API Collapse	<b>22.330 psi</b>
Yield Torque	<b>28.000 lbs./ft.</b>
<b>Connection Data</b>	
Connection type	<b>533</b>
Box OD (Turned)	<b>4 160"</b>
ID of tool-joint pin / box	<b>2,498"</b>
Make-up Loss	<b>4,49 in</b>
Pin OD (Turned)	<b>3,973 in</b>
Threads pr in	<b>2,94</b>
Critical Section Area	<b>N/A</b>
Tension Efficiency	<b>100 %</b>
Compression Rating	<b>100 %</b>
Make-up torque minimum	<b>7,800 ft.lbs.</b>
Target	<b>9,000 ft.lbs.</b>
Make-up torque maximum	<b>N/A</b>
Yield Torque	<b>17,500 ft.lbs.</b>
<b>Blanking Dimentions (in inches)</b>	
Pin ID	<b>2,498 +- 0,010</b>
Pin OD	<b>3,973 +- 0,010</b>
Box OD	<b>4,160 +- 0,010</b>
Box ID	<b>2,738 MAX</b>
Length w/o Recut	<b>5,00 MIN</b>
Length with Recut	<b>7,25 MIN</b>
Effective length of drillpipe from	<b>30 to 31 ft.</b>