

Equipment No's: Ref. Enclosed page

Spec. No.: DP-5-08

TECHNICAL SPECIFICATIONS

5" OD Drill Pipe, G-105, NC-50 Conn's.

New
Premium

80% Remaining Body Wall

DESCRIPTION

Type IEU, 19.5 #
 Range 2
 Conventional=welded T-J. / Integral=Monoblock Conventional

TUBE DATA

Material grade				G-105	
Internal plastic coating				TK-34P	
Tube body OD x ID	inch	5,000	4,276	4,855	4,276
Wall thickness, nominal	inch	0,362			0,290
Cross Sectional Area	inch ²	5,275			4,152
Polar Sectional Modulus	inch ³	11,415			8,949
Tensile yield pipe	lbf	553 800			436 000
	kN	2 463			1 939
Torsional yield pipe	lbf-ft	57 600			45 200
	kNm	78,1			61,3
80% Torsional Yield	lbf-ft	46 080			36 160
	kNm	62,5			49,0

CONNECTIONS DATA

Connection type				NC-50 Standard	
Material grade				120ksi	
Hardbanding				Armacor-M	
OD x ID	inch	6,625	3,625/3,25	6,313	3,625/3,25
B.S.R.	x : 1	2,80/2,43			2,28/1,97
Tensile yield tooljoint	lbf	1 250 000			1 158 000
	kN	5 560			5 151
Torsional yield tooljoint	lbf-ft	51 700			47 300
	kNm	70,1			64,1
Make up torque (Max.)	lbf-ft	31 000			28 000
	kNm	42,0			38,0

OPERATIONAL DATA

Tool-joint/Drill-pipe torsional ratio		0,90		1,14	
Drift diameter	inch		3,125		
Type of elevator shoulder			18°		
Burst pressure	psi	13 300			12 200
	Mpa	92			84
Collapse pressure	psi	13 000			8 800
	MPa	90			61
Adjusted weight	lbs/ft		22,0		
	kg/mtr		32,7		
Approx weight each joint	lbs		695		
	kg		315		
Capacity	gal/ft		0,73		
	ltr/mtr		9,04		
Open end displacement	gal/ft		0,35		
	ltr/mtr		4,35		
Closed end displacement	gal/ft		1,08		
	ltr/mtr		13,39		
Built In Length (shoulder to shoulder)	ft		31,60		
	mtr.		9,63		

Calculated using nominal OD & ID. Safety & Dope friction factor used: 1.0

Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !

<http://www.ows.no/Legal-Notice>

Docs. # 1055727

Frb - 11.12.2014



ODFJELL WELL SERVICES

A PART OF ODFJELL DRILLING

<i>String number:</i>	<i>Joints:</i>	<i>Individual serial numbers:</i>
OWS-DP-8502	127	A617-001 to A617-985
OWS-3673	127	OWS-001 to OWS-127