



3-1/8" Slick Drillcollar Specification Sheet

Technical for DC's	Unit	3 1/8" OD
Shoulder type		None
Overall Length (New)	ft <i>mtr</i>	31 <i>9,45</i>

Elevator & Slip recess OD	inch	NA
Elevator & Slip recess length	inch	NA
Spiral length	inch	NA
Box tong space	inch	NA
Pin tong space	inch	NA

Open End Displacement	gal/ft <i>l/m</i>	0,307 <i>3,83</i>
Capacity	gal/ft <i>l/m</i>	0,092 <i>1,15</i>
Closed End Displacement	gal/ft <i>l/m</i>	0,399 <i>4,98</i>

Weight	lbs <i>kg</i>	650 <i>295</i>
Weight/Length	lbs/ft <i>kg/mtr</i>	21,0 <i>31,2</i>

Connection	API	2-7/8" HT-PAC
OD	inch	3,125
ID	inch	1,5
BB+SRG (NS-2)		NA
Connection Tensile Capacity	lbf <i>kn</i>	250 300 <i>1 113</i>
Connection Torsional Capacity	ft-lbs <i>nm</i>	7 800 <i>10 575</i>
Make up torque (Max.)	ft-lbs <i>nm</i>	4 700 <i>6 372</i>

Body

Material Grade	AISI-4145H, 110ksi (API)	
Tensile Capacity (New)	lbf <i>kn</i>	649 303 <i>2 888</i>
Torsional Capacity (New)	ft-lbs <i>nm</i>	30 012 <i>40 691</i>
Drift diameter	inch	1,375



Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !