



9 1/2" Drillcollar Specification Sheet

Technical for DC's	Unit	9 1/2"
Shoulder type	Taper	18°
Overall Length (New)	ft <i>mtr</i>	31 <i>9,45</i>

Elevator & Slip recess OD	inch	6,625
Elevator & Slip recess length	inch	63,0
Spiral length	inch	221,1
Box tong space	inch	23,6
Pin tong space	inch	29,5

Displacement	gal/ft <i>l/m</i>	2,8804 <i>35,773</i>
Capacity	gal/ft <i>l/m</i>	0,3671 <i>4,559</i>
Closed End Displacement	gal/ft <i>l/m</i>	3,2475 <i>40,332</i>

Weight	lbs <i>kg</i>	5 872 <i>2 663</i>
Weight/Length	lbs/ft <i>kg/mtr</i>	189,42 <i>281,89</i>

Connection	API	7 5/8" Reg
OD	inch	9,500
ID	inch	3,000
BB+SRG (NS-2)		Yes
Connection Tensile Capacity	lbf <i>kn</i>	2 220 651 <i>9 878</i>
Connection Torsional Capacity	ft-lbf <i>nm</i>	136 381 <i>184 908</i>
Make up torque (with SRG)	ft-lbf <i>nm</i>	77 489 <i>105 061</i>

Body

Material Grade	AISI 4145-H mod.	
Tensile Capacity (New)	lbf <i>kn</i>	2 622 139 <i>11 664</i>
Torsional Capacity (New)	ft-lbs <i>nm</i>	289 417 <i>392 397</i>



Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !