

Equipment No's: Ref. Enclosed page

Spec. No.: DP-5.5-01

TECHNICAL SPECIFICATIONS

5-1/2" OD Drill Pipe, S-135, 5-1/2" FH. Conn's.

New
Premium

80% Remaining Body Wall

DESCRIPTION

 Type IEU, 21,90 #
 Range 3
 Conventional=welded T-J. / Integral=Monoblock Conventional

TUBE DATA

Material grade				S-135	
Internal plastic coating				TK-34P	
Tube body OD x ID	inch	5,500	4,778	5,355	4,778
Wall thickness, nominal	inch	0,361		0,289	
Cross Sectional Area	inch ²	5,828		4,592	
Polar Sectional Modulus	inch ³	14,062		11,042	
Tensile yield pipe	lbf	786 800		619 900	
	kN	3 500		2 757	
Torsional yield pipe	lbf-ft	91 280		71 680	
	kNm	123,8		97,2	
80% Torsional Yield	lbf-ft	73 024		57 344	
	kNm	99,0		77,7	

CONNECTIONS DATA

Connection type				5-1/2" FH. Standard	
Material grade				120 ksi	
Hardbanding				Arnco-300XT	
OD x ID	inch	7,250	3,500	6,719	3,500
B.S.R.	x : 1	2,25		1,60	
Tensile yield tooljoint	lbf	1 598 000		1 036 300	
	kN	7 108		4 610	
Torsional yield tooljoint	lbf-ft	72 480		46 090	
	kNm	98,3		62,5	
Make up torque (Max.)	lbf-ft	43 500		27 700	
	kNm	59,0		37,6	

OPERATIONAL DATA

Tool-joint/Drill-pipe torsional ratio		0,79		1,01	
Drift diameter	inch		3,375		
Type of elevator shoulder			18°		
Burst pressure	psi	15 500		14 200	
	Mpa	107		98	
Collapse pressure	psi	12 700		7 500	
	MPa	88		52	
Adjusted weight	lbs/ft		23,6		
	kg/mtr		35,1		
Approx weight each joint	lbs		1 079,7		
	kg		489,7		
Capacity	gal/ft		0,89		
	ltr/mtr		11,08		
Open end displacement	gal/ft		0,36		
	ltr/mtr		4,47		
Closed end displacement	gal/ft		1,25		
	ltr/mtr		15,55		
Built In Length (shoulder to shoulder)	ft		45,75		
	mtr.		13,94		

Calculated using nominal OD & ID. Safety & Dope friction factor used: 1.0

Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !

<http://www.ows.no/Legal-Notice>

Docs. # 1056725

Frb - 11.12.2014



ODFJELL WELL SERVICES

A PART OF ODFJELL DRILLING

<i>String number:</i>	<i>Joints:</i>	<i>Individual serial numbers:</i>
OWS-DP-5121	269	VIS-001 to VIS-269