

SPECIFICATION SHEET

Equipment

4 - 3/4" Drillcollar, Non-Mag. Slick

SPECIFICATION

Technical for DC's	Unit	4 3/4"
Shoulder Type	Taper	Slick
Overall Length (New)	ft	31
	<i>mtr</i>	9,45

Elevator & Slip Recess OD	inch	NA
Elevator & Slip Recess Length	inch	NA
Spiral Length	inch	NA
Box Tong Space	inch	NA
Pin Tong Space	inch	NA

Displacement	gal/ft	0,716
	<i>l/m</i>	8,89
Capacity	gal/ft	0,207
	<i>l/m</i>	2,57
Closed End Displacement	gal/ft	0,923
	<i>l/m</i>	11,46

Weight	lbs	1 442
	<i>kg</i>	654
Weight/Lenght	lbs/ft	46,6
	<i>kg/mtr</i>	69,4

Connection	API	NC-38
OD	inch	4,75
ID	inch	2,25
BB+SRG (NS-2)		Yes
Connection Tensile Capacity	lbf	465 000
	<i>kN</i>	2 068
Connection Torisional Capacity	ft-lbf	16 200
	<i>kNm</i>	21,9
Make up torque (with SRG)	ft-lbf	9 200
	<i>kNm</i>	12,5

BODY

Material Grade	P-530	
Tensile Capacity (New)	lbf	1 511 900
	<i>kN</i>	6 725
Torsional Capacity (New)	ft-lbs	105 700
	<i>kNm</i>	143,3

Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !

