

SPECIFICATION SHEET

Equipment

3 - 1/8" Slick Drillcollar

SPECIFICATION

Technical for DC's	Unit	3 1/8" OD
Shoulder Type		None
Overall Length (New)	ft <i>mtr</i>	31 9,45

Elevator & Slip Recess OD	inch	NA
Elevator & Slip Recess Length	inch	NA
Spiral Length	inch	NA
Box Tong Space	inch	NA
Pin Tong Space	inch	NA

Open End Displacement	gal/ft <i>l/m</i>	0,307 3,83
Capacity	gal/ft <i>l/m</i>	0,092 1,15
Closed End Displacement	gal/ft <i>l/m</i>	0,399 4,98

Weight	lbs <i>kg</i>	650 295
Weight/Lenght	lbs/ft <i>kg/mtr</i>	21,0 31,2

Connection	API	2-7/8" HT-PAC
OD	inch	3,125
ID	inch	1,5
BB+SRG (NS-2)		NA
Connection Tensile Capacity	lbf <i>kn</i>	250 300 1 113
Connection Torisional Capacity	ft-lbs <i>nm</i>	7 800 10 575
Make up Torque (Max.)	ft-lbs <i>nm</i>	4 700 6 372

BODY

Material Grade	AISI-4145H, 110ksi (API)	
Tensile Capacity (New)	lbf <i>kn</i>	649 303 2 888
Torsional Capacity (New)	ft-lbs <i>nm</i>	30 012 40 691
Bottom Hole Length	inch	1,375

Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !

