

## SPECIFICATION SHEET

Equipment

### 6 - 3/4" Drillcollar, Non-Mag. Slick

#### SPECIFICATION

Technical for DC's	Unit	6 3/4"
Shoulder Type	Taper	Slick
Overall Length (New)	ft	31
	<i>mtr</i>	9,45

Elevator & Slip Recess OD	inch	NA
Elevator & Slip Recess Length	inch	NA
Spiral Length	inch	NA
Box Tong Space	inch	NA
Pin Tong Space	inch	NA

Open End Displacement	gal/ft	1,540
	<i>l/m</i>	19,13
Capacity	gal/ft	0,324
	<i>l/m</i>	4,02
Closed End Displacement	gal/ft	1,864
	<i>l/m</i>	23,15

Weight	lbs	3 102
	<i>kg</i>	1 407
Weight/Lenght	lbs/ft	100,27
	<i>kg/mtr</i>	149,2

<b>Connection</b>	<b>API</b>	<b>NC-50</b>
OD	inch	6,75
ID	inch	2,813
BB+SRG (NS-2)		Yes
Connection Tensile Capacity	lbf	987 800
	<i>kN</i>	4 393
Connection Torisional Capacity	ft-lbf	45 900
	<i>kNm</i>	62,2
Make up torque (with SRG)	ft-lbf	26 000
	<i>kNm</i>	35,2

#### BODY

Material Grade	P-530	
Tensile Capacity (New)	lbf	3 252 000
	<i>kN</i>	6 725
Torsional Capacity (New)	ft-lbs	105 700
	<i>kNm</i>	143,3

Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !

