

SPECIFICATION SHEET

Equipment

4 - 3/4" Drillcollar

SPECIFICATION

Technical for DC's	Unit	4 3/4"
Shoulder Type	Taper	18°
Overall Length (New)	ft <i>mtr</i>	31 9,45

Elevator & Slip Recess OD	inch	3 1/2"
Elevator & Slip Recess Length	inch	66,9
Spiral Length	inch	237,5
Box Tong Space	inch	29,5
Pin Tong Space	inch	29,5

Open End Displacement	gal/ft <i>l/m</i>	0,6203 7,703
Capacity	gal/ft <i>l/m</i>	0,2065 2,565
Closed End Displacement	gal/ft <i>l/m</i>	0,8268 10,269

Weight	lbs <i>kg</i>	1 264 573
Weight/Lenght	lbs/ft <i>kg/mtr</i>	40,77 60,67

Connection	API	NC-38
OD	inch	4,75
ID	inch	2,25
BB+SRG (NS-2)		Yes
Connection Tensile Capacity	lbf <i>kn</i>	465 181 2 069
Connection Torisional Capacity	ft-lbs <i>nm</i>	16 296 22 094
Make up Torque (with SRG)	ft-lbs <i>nm</i>	9 259 12 553

BODY

Material Grade	AISI 4145-H mod.	
Tensile Capacity (New)	lbf <i>kn</i>	539 961 2 401,87
Torsional Capacity (New)	ft-lbs <i>nm</i>	36 922 50 060

Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !

