

## SPECIFICATION SHEET

Equipment

### 9 - 1/2" Drillcollar, Non-Mag. Slick

#### SPECIFICATION

Technical for DC's	Unit	9 1/2"
Shoulder Type	Taper	Slick
Overall Length (New)	ft	31
	<i>mtr</i>	9,45

Elevator & Slip Recess OD	inch	NA
Elevator & Slip Recess Length	inch	NA
Spiral Length	inch	NA
Box Tong Space	inch	NA
Pin Tong Space	inch	NA

Displacement	gal/ft	3,324
	<i>l/m</i>	41,28
Capacity	gal/ft	0,368
	<i>l/m</i>	4,57
Closed End Displacement	gal/ft	3,692
	<i>l/m</i>	45,85

Weight	lbs	6 694
	<i>kg</i>	3 036
Weight/Lenght	lbs/ft	216,37
	<i>kg/mtr</i>	322,0

Connection	API	7-5/8" Reg.
OD	inch	9,500
ID	inch	3,000
BB+SRG (NS-2)		Yes
Connection Tensile Capacity	lbf	2 220 600
	<i>kN</i>	9 878
Connection Torisional Capacity	ft-lbf	132 500
	<i>kNm</i>	179,6
Make up torque (with SRG)	ft-lbf	77 500
	<i>kNm</i>	105,0

#### BODY

Material Grade	P-530	
Tensile Capacity (New)	lbf	6 380 000
	<i>kn</i>	28 379
Torsional Capacity (New)	ft-lbs	801 000
	<i>kNm</i>	1 086,0

Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !

