

SPECIFICATION SHEET

Equipment

6 1/2 & 6 3/4" Drillcollar

SPECIFICATION

Technical for DC's	Unit	6 1/2"	6 3/4"
Shoulder Type	Taper	18°	18°
Overall Length (New)	ft	31	31
	<i>mtr</i>	9,45	9,45

Elevator & Slip Recess OD	inch	5,0	5,0
Elevator & Slip Recess Length	inch	66,9	66,9
Spiral Length	inch	235,8	234,4
Box Tong Space	inch	29,5	29,5
Pin Tong Space	inch	29,5	29,5

Displacement	gal/ft	1,2396	1,3479
	<i>l/m</i>	15,395	16,740
Capacity	gal/ft	0,3227	0,3227
	<i>l/m</i>	4,008	4,008
Closed End Displacement	gal/ft	1,5623	1,6707
	<i>l/m</i>	19,403	20,748

Weight	lbs	2 527	2 748
	<i>kg</i>	1 146	1 246
Weight/Lenght	lbs/ft	81,52	88,65
	<i>kg/mtr</i>	121,31	131,92

Connection	API	NC-50	NC-50
OD	inch	6,5	6,75
ID	inch	2,8126	2,8126
BB+SRG (NS-2)		Yes	Yes
Connection Tensile Capacity	lbf	987 871	987 871
	<i>kn</i>	4 394	4 394
Connection Torisional Capacity	ft-lbs	45 491	45 968
	<i>nm</i>	61 677	62 324
Make up Torque (with SRG)	ft-lbs	25 847	26 118
	<i>nm</i>	35 044	35 411

BODY

Material Grade	AISI 4145-H mod.		
Tensile Capacity (New)	lbf	1 283 834	1 283 834
	<i>kn</i>	5 711	5 711
Torsional Capacity (New)	ft-lbs	116 818	116 818
	<i>nm</i>	158 384	158 384

Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !

