

SPECIFICATION SHEET

Equipment

9 - 1/2" Drillcollar

SPECIFICATION

Technical for DC's	Unit	9 1/2"
Shoulder Type	Taper	18°
Overall Length (New)	ft <i>mtr</i>	31 9,45

Elevator & Slip Recess OD	inch	6,625
Elevator & Slip Recess Length	inch	63,0
Spiral Length	inch	221,1
Box Tong Space	inch	23,6
Pin Tong Space	inch	29,5

Displacement	gal/ft <i>l/m</i>	2,8804 35,773
Capacity	gal/ft <i>l/m</i>	0,3671 4,559
Closed End Displacement	gal/ft <i>l/m</i>	3,2475 40,332

Weight	lbs <i>kg</i>	5 872 2 663
Weight/Lenght	lbs/ft <i>kg/mtr</i>	189,42 281,89

Connection	API	7 5/8" Reg
OD	inch	9,500
ID	inch	3,000
BB+SRG (NS-2)		Yes
Connection Tensile Capacity	lbf <i>kn</i>	2 220 651 9 878
Connection Torisional Capacity	ft-lbs <i>nm</i>	136 381 184 908
Make up Torque (with SRG)	ft-lbs <i>nm</i>	77 489 105 061

BODY

Material Grade	AISI 4145-H mod.	
Tensile Capacity (New)	lbf <i>kn</i>	2 622 139 11 664
Torsional Capacity (New)	ft-lbs <i>nm</i>	289 417 392 397

Values herein is meant as guidelines only. Odfjell will not be held liable for any damage or injuries !

