

SPECIFICATION SHEET

Equipment

17" x 32" HOLE OPENER

SPECIFICATION

| | |
|-------------------------------------|---------------|
| Pilot Hole Diameter | 17" |
| Pilot Hole Stabilizer Blade Length | 12,05" |
| Hole Opener Diameter | 32" |
| Hole Opener Stabilizer Blade Length | 22" |
| Cutter Quantity | 3" |
| Fish Neck Length | 46" |
| Bottom Hole Length | 17" |
| Fishing Neck Diameter | 9.5" |
| ID | 3" |
| Overall Length | 132" |
| Cutter Type | 14" TCI |
| Bearing Type | Sealed Roller |
| Inner Insert Shape | Chisel |
| Gauge Insert Shape | Dome |
| Jets to Cutters | 3 |
| Jets Under Cutters | 0 |
| Jets to Reamed Hole Facing Rig | 3 |
| Weight | 3600kg |

ENGINEERING FEATURES

| |
|---|
| * Interchangeable Cutting Elements – Milled Tooth, TCI and PDC |
| * Patented Cutter Retention System |
| * Under Cutter Anti-Balling Jets to Increase Cuttings Removal Around Cutters If Requested |
| * Field Replaceable 17", 17 ½" or 26" Stabilizer sleeve |

RECOMMENDED DRILLING PARAMETERS

| | |
|---------------------------------------|--------------------------|
| WEIGHT ON HOLE OPENER @ 80 to 100 RPM | 4 to 20 Tonnes Per Cuter |
| ROTARY SPEED | 25 - 150 RPM |
| FLOW RATE | 1800 – 7000 LPM |

NOTE - At 150RPM Cuttings Generated will be High and therefore Mud Flow will also need to be High with Large Jets to Hole Gauge

